



# XMP44

SourceCon™ professional modular audio system

## ► Features

- Fully flexible modular structure
- Stores up to 4 SourceCon™ modules
- 2.8" TFT display with intuitive user interface
- Wide variation of modules separately available
- Front USB interface for each module (4x)
- Control through front panel, app & web interface
- RS-232 and TCP/IP remote control connections
- Built-in pre-listening speaker
- Simultaneous operation for all 4 modules

## ► Applications

- Clubs & pubs
- Restaurants & bars
- Warehouses & retail stores
- Public & office buildings
- Houses of worship
- ...



The XMP44 is a professional modular audio system with 4 SourceCon™ interface card slots where to a wide variation of optional modules can be installed. The variety of available modules ranges from FM tuners to DAB&DAB+ tuners, internet radio tuners, voice file interfaces and many more.

The flexible architecture allows any project combination up to four sources, resulting in a truly versatile solution that will live up the needs for any user taking high regard of crystal clear audio reproduction. Simultaneous operation for all four modules makes it a compact multi-source system which is the perfect expansion for any multi-zone audio system.

The front panel of the system accommodates a 2.8" TFT display in combination with a push rotary function dial and 4 tactile pushbuttons. The controls and indicators on the front panel of the unit are guaranteeing an intuitive and user friendly operation, allowing hassle free operation and configuration to even unexperienced users. Four USB interfaces (one for each module) are enabling playback or storage of media and voice file, while pre-listening for each output is possible through a built-in PFL speaker with individual volume control.

Both RS-232 and TCP/IP communication ports are implemented, allowing system integration with any home or industrial automation system. Using the freely available Audac Touch™ application for smart devices guarantees total system control and configuration from any device on any location and at any time.

## ► Specifications

SYSTEM SPECIFICATIONS	
In & outputs	4 x SourceCon™ interface card slots USB interface (4 x)
Control	Front panel
	RS232
	TCP/IP
	Audac Touch™ app
Frequency response	20 Hz - 20 kHz
Display	2.8" Graphical LCD
Monitoring	Front PFL speaker with vol control
Power supply	Switching mode
Power source	110 ~ 240V AC / 50 ~ 60 Hz
Operating temperature	0° ~ 40° C at 95% humidity
Power consumption	2 Watt (without module installed)
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	482 x 44 x 330 mm
Weight net	3.4 Kg
Mounting	19"
Unit height	1 HE
Construction	Steel
Colour	Black
SHIPPING & ORDERING	
Packaging	Cardboard box
Shipping weight and volume	4.75 Kg - 0.028 Cbm
Compatible devices	DMP40 DAB/DAB+/FM tuner module
	FMP40 Voice file interface module
	IMP40 Internet radio module
	MMP40 Media player/recorder module
	TMP40 FM tuner module
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continuously improve our products.	