



WX802MK2

Universal wall speaker 8"

Highlights:

- 1" Dome tweeter
- 8" Low frequency loudspeaker
- Vertical and horizontal mounting
- 100V and low impedance connection possibility
- Multi-tapping 100V line transformer
- Terminal block connection
- Aluminum grill

The WX802MK2 is a powerful 2-way performance speaker suitable for a wide variety of applications, ensuring true-to-nature, high fidelity reproduction of music and speech. It is fitted with a 1" dome tweeter and an 8" low-frequency loudspeaker, capable of delivering a power of 70 Watt. It can be used in standard 16 Ohm systems but also in 100V PA systems with power taps for 60 Watt, 30 Watt and 15 Watt. The elegant shaped synthetic enclosure is available in two different colours (black & white), making it blend into any environment, going from standard indoor home to special indoor design interiors. The included mounting bracket allows horizontal and vertical mounting as well as focusing of the speaker, and an integrated advanced protection network protects the tweeter against overload.

This new series retains all its strengths but has also been upgraded in a few specific areas with installer convenience and durability in mind. The connection of the indoor speakers has been changed to a terminal block, which makes it easier to install a single WXMK2 wall speaker. In addition, it can also be easily looped through with several speakers. Both indoor and outdoor versions are now equipped with an elegant rotatable AUDAC logo.

Applications:


- Retail
- Clubs, bars, restaurants
- Residential
- Corporate spaces



Impedance:



Voltage:



System specifications:

Speaker type		2-way
Max. Power		140 W
RMS Power		70 W
Impedance		16 Ω
Line Transformer Tappings	1	60 W / 167 Ω
	2	30 W / 333 Ω
	3	15 W / 667 Ω
Sensitivity (1W/1m)		89 dB
Sound Pressure (Max. W/1m)	@ 16 Ω	108 dB
	@ 100 V	106 dB
Frequency	Response (\pm 3 dB)	60 Hz - 17 kHz
	Range (-10 dB)	50 Hz - 20 kHz
Crossover	Frequency	2.4 kHz
	Type	Passive built-in
Dispersion	Horizontal	110°
	Vertical	110°
Drivers	HF	1"
	LF	8"

Product Features:

Dimensions	270 x 360 x 215 mm (W x H x D)
Weight	7.500 kg
Operating temperature	-25 °C ~ 70 °C
Construction	ABS
Mounting & handling	Mounting bracket
Front finish	Aluminium grill
Colours	Black (RAL9005) (WX802MK2/B)
	White (RAL9003) (WX802MK2/W)

Architects' and Engineers' Specifications:

The loudspeaker shall be a surface-mount 2-way type, consisting of an 8" woofer and 1" tweeter which are built in an ABS enclosure with finely perforated front grill and fitted with a line transformer allowing it to be used on both low impedance (16 Ohm) and 100 Volt distributed lines. It shall be vertically and horizontally mountable using the supplied mounting bracket. It shall have an RMS power handling of 70 Watt with a maximum power handling of 140 Watt and the frequency response (± 3 dB) shall range from 60 Hz to 17 kHz. The sensitivity shall be 89 dB when measured with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level shall be 108 dB. The loudspeaker shall have an impedance of 16 Ohm, a 100V line transformer and a passive built-in crossover network with a crossover frequency of 2.4 kHz. The transformer shall have multiple tapings for 60 Watt, 30 Watt and 15 Watt which are selectable, including the 16 Ohm bypass, using a rotary switch on the rear of the enclosure. The loudspeaker enclosure shall be 270 mm high, 360 mm wide and 215 mm deep and the weight shall not exceed 7.5 Kg.